



Artillery Release Form

Please print this document using your browser's **"PRINT"** button or select print from the file menu. Fill in the form and mail it along with your cannon order to the address below. If you have any questions please contact us at orders@dixiegunworks.com or call 901-885-0700.

NOTICE: READ, SIGN AND MAIL WITH YOUR ORDER!

When ordering any of our 1/4, 1/2, 2/3, 3/4 or full scale cannons, the customer is required to sign a form of necessary safety rules and powder loads. Please make a copy of the form (below), sign it and mail it in with your order. You must return a copy of the form, signed, before your order can be shipped. This form is necessary for cannons with carriages or barrels only.

BASIC SAFETY REGULATIONS FOR SHOOTING MUZZLELOADING ARTILLERY

A Portion of the following regulations was taken from "Safety Rules and Procedures for Shooting Muzzleloading Artillery" compiled by The Artilleryman magazine. You may send for the pamphlet free of charge from The Artilleryman, Monarch Hill Rd., RT #1, Box 36, Tunbridge, VT 05077.

1. Powder Charge Preparations: Black powder (only) should not exceed 2 oz. Fg per any 2 1/4" bore diameter.
2. Pre-measured powder charges should be wrapped in heavy duty aluminum foil, double thickness.
3. All crew members should wear ear protection devices.
4. No one should cross in front of the muzzle at any time during the cleaning, loading, or firing procedures.
5. The ammunition box shall be attended at all times, or be locked. The interior shall be lined with a non-sparking material and the box itself shall be stoutly constructed of wood or metal.
6. No smoking at any time on the line.
7. No drinking alcoholic beverages on the line.

8. Projectiles shall be constructed so that they easily pass through a sizing gauge with finger or thumb pressure only. The sizing gauge to be a length at least 1.5 times the length of the projectile and an inside dia. no greater than bore diameter when the tube was new.

9. It is necessary to swab the bore with a wet mop between shots. ALWAYS ALLOW 15 MINUTES FOR ELAPSE BETWEEN FIRING AND RELOADING THE NEXT POWDER CHARGE.

Signature of Purchaser

Date

Complete Address

* Print this document and keep the bottom page for your records. You **MUST** sign and mail the first 2 pages with your order to the following address:

**DIXIE GUN WORKS
P.O. BOX 130
UNION CITY, TN 38281**



BASIC SAFETY REGULATIONS FOR SHOOTING MUZZLELOADING ARTILLERY

A Portion of the following regulations was taken from "Safety Rules and Procedures for Shooting Muzzleloading Artillery" compiled by The Artilleryman magazine. You may send for the pamphlet free of charge from The Artilleryman, Monarch Hill Rd., RT #1, Box 36, Tunbridge, VT 05077.

1. Powder Charge Preparations: Black powder (only) should not exceed 2 oz. Fg per any 2 1/4" bore diameter.
2. Pre-measured powder charges should be wrapped in heavy duty aluminum foil, double thickness.
3. All crew members should wear ear protection devices.
4. No one should cross in front of the muzzle at any time during the cleaning, loading, or firing procedures.
5. The ammunition box shall be attended at all times, or be locked. The interior shall be lined with a non-sparking material and the box itself shall be stoutly constructed of wood or metal.
6. No smoking at any time on the line.
7. No drinking alcoholic beverages on the line.
8. Projectiles shall be constructed so that they easily pass through a sizing gauge with finger or thumb pressure only. The sizing gauge to be a length at least 1.5 times the length of the projectile and an inside dia. no greater than bore diameter when the tube was new.
9. It is necessary to swab the bore with a wet mop between shots. **ALWAYS ALLOW 15 MINUTES FOR ELAPSE BETWEEN FIRING AND RELOADING THE NEXT POWDER CHARGE.**

* Keep this portion for your records.